

# MX12F 1/2" flowmeter series



1/2" Oval gear flow meter designed for the measurement of industrial Fuels and Oils.

- Aluminium construction
- Max flow rate 30 LPM / 8 GPM
- Temperature up to 80°C
- Accuracy 0.5% Pulse
- Available with BSP or NPT process connections
- Suitable for high viscosity fluids

### Materials of Construction

<b>Meter Body</b>	Aluminium
<b>Rotor</b>	PPS (Ryton) * Standard option
<b>Seals</b>	FKM (Viton™)

### Technical Specifications

<b>Flow Rate</b>	<b>&lt;5cps</b> 3-25 L/min	<b>&gt;5cps</b> 2-30 L/min
<b>Temperature</b>	-40 - 80°C	
<b>Pressure</b>	1,000 psi	
<b>Accuracy</b>	+/- 0.5%	
<b>Repeatability</b>	+/- 0.03%	
<b>Nominal K-Factor</b>	112 pulses per ltr	

### Display and Output Options

<b>Standard</b>	Pulse Output	1x Reed/1x Hall Effect
<b>PR</b>	LC display (12mm)	Display Only
<b>PRA</b>	LC display (12mm)	Scaled Pulse, 4-20mA and Hi/Lo Flow Alarm
<b>ER</b>	LC display (17mm)	Display Only
<b>ERA</b>	LC display (17mm)	Scaled Pulse, 4-20mA output (passive)
<b>ERS</b>	LC display (17mm)	Net Use Function - input A-B (remote mount only)

### Accessories

- Stainless Steel Y Strainer - 250 micron (60 mesh)
- Service/repair kits available upon request

### Design Specifications

<b>Process Connections</b>	<b>Threaded</b>
	1/2" BSP
	1/2" NPT